

APOLLO SUPERFLEX 2

(Cod. SF)



+50°C

-40°C



Tubo de PVC/NBR de color negro, reforzado con espiral de PVC rígido antichoque gris. Formulación específica para climas muy rígidos que lo convierten en un tubo mejor que otros análogos en PVC usados comunmente. Estructura con espiral a vista que garantiza un deslizamiento fácil sobre el terreno. Versión antiestática (con hilo de cobre) bajo pedido.

- Óptimo para aspiración impulsión de líquidos en general y especialmente para la aspiración de residuos y descarga de aguas negras.


PVC/NBR hose reinforced with a gray anti-shock rigid PVC spiral. Its particular mixed rubber nitrilic formulation gives it a high flexibility at extreme low temperatures. Its profile with a slightly protruding spiral guarantees an easy dragging on the ground and an easy and safe connection. Antistatic version with copper wire on request.

- Suction and delivery of liquids and industrial water in general; ideal to be used on tank trucks, even at extremely low temperatures.



Espiral de PVC rígido antichoque
Anti-shock rigid PVC spiral

Tubo de PVC/NBR / PVC/NBR hose



Ficha técnica / Technical data

Código	Ø int.	Min esp.	Max esp.	Peso	P.T.	P.R.	Vacio	R. de curvatura	Lg. Rollo
Code	Ø Int.	Min wall th.	Max wall th.	Weight	W.P.	B.P.	Vac.	Bending	Coil lgth.
	mm/inch	mm	mm	g/m	[bar]	[bar]	m H ₂ O	mm	m
SF010520000000	50,8/2"	4,4	4,9	970	3,3	10	7	160	50
SF010550000000	55	4,6	5,1	1100	3,3	10	7	160	50
SF010600000000	60	4,8	5,3	1260	3,0	9	7	200	50
SF010630000000	63,5/2.1/2"	4,9	5,5	1380	3,0	9	7	210	50
SF010650000000	65	5,0	5,6	1440	3,0	9	7	210	50
SF010700000000	70/2.3/4"	5,1	5,7	1530	3,0	9	7	225	50
SF010760000000	76,2/3"	5,1	5,8	1670	3,0	9	7	250	50
SF010800000000	80	5,1	6,8	1930	2,5	7,5	7	270	50
SF010900000000	90	5,2	7,0	2220	2,5	7,5	7	300	30
SF011020000000	102/4"	5,9	7,6	2770	2,2	6,5	6	335	30
SF011050000000	105	6,0	7,6	2870	2,2	6,5	6	335	30
SF011100000000	110	6,1	7,6	2990	2,0	6	6	360	30
SF011270000000	127/5"	6,3	7,8	3540	1,8	5,5	6	410	30
SF011520000000	152,4/6"	7,4	9,0	5000	1,5	4,5	6	500	20

*Disponible bajo demanda. Consulte con ventas para más información y cantidades / *Available on request, contact our sales office for more info and quantities

Los datos técnicos aquí reportados fueron medidos a 23°C con 50% de humedad / The technical data here reported were measured at 23°C with 50% humidity