



EOLO PU EST ASW

(Cod. OU 86)



Tubo transparente con la pared de TPU ESPECIAL a base éster con propiedades antiestáticas permanentes ($R < 10^9$ Ohm/m) que facilitan la continua disipación de las cargas electrostáticas, además de mejorar el flujo, permite que se desprendan fácilmente los residuos de la pared del tubo. Espiral de refuerzo de PVC rígido antichoque de color gris oscuro. Buena resistencia a la abrasión y a la flexión. Grosor de pared 0,4 mm - 0,8 mm. Versión antiestática (con hilo de cobre) según pedido.


- Aspiración de polvos, gránulos y substancias abrasivas

Transparent ester based TPU hose, reinforced with a dark grey anti-shock rigid PVC spiral. The special TPU formulation makes the hose wall permanent antistatic ($R < 10^9$ Ohm/m), as it enables a continuous dissipation of electrostatic charges, as well as an optimization of flow properties (as a consequence of an easier detachment of the media conveyed from the wall). Excellent resistance to abrasion and torsion. Wall thickness from 0,4 to 0,8 mm. Available on request the AS version with copper wire.

- Suction of powders, granulates, chips and abrasive solids

Espiral de PVC rígido anti choque / Anti-shock rigid PVC spiral

TPU a base de éster / Ester based TPU hose



Ficha técnica / Technical data

Código	Ø int.	Min esp.	Max esp.	Peso	Vacio	R. de curvatura	Lg. Rollo	Vol.
Code	Ø Int.	Min wall th.	Max wall th.	Weight	Vac.	Bending	Coil lgth.	Vol.
	mm/inch	mm	mm	g/m	m H ₂ O	mm	m	m ³
OU860130000000	13*	0,4	2,8	80	2,5	20	20	0,013
OU860160000000	16*	0,4	2,8	100	2,5	25	20	0,018
OU860190000000	19,1*3/4"	0,4	2,8	120	2,5	25	20	0,022
OU860200000000	20	0,4	2,8	120	2,5	25	20	0,025
OU860220000000	22*	0,4	2,8	130	2,5	28	20	0,028
OU860250000000	25	0,4	2,8	150	2,5	30	20	0,034
OU860300000000	30	0,4	2,8	170	2,5	35	20	0,051
OU860320000000	31,8/1.1/4"	0,4	2,9	190	2	35	20	0,054
OU860350000000	35	0,5	3,0	220	2	45	20	0,059
OU860380000000	38,1/1.1/2"	0,5	3,1	250	2	50	20	0,080
OU860400000000	40	0,5	3,1	260	2	60	20	0,083
OU860450000000	45	0,5	3,2	300	2	65	20	0,099
OU860500000000	50*	0,5	3,4	350	2	70	20	0,109
OU860520000000	50,8/2"	0,5	3,4	360	2	70	20	0,111
OU860550000000	55*	0,5	3,6	420	2	75	20	0,119
OU860600000000	60	0,5	3,8	500	1,6	80	20	0,173
OU860630000000	63,5/2.1/2"	0,5	3,9	550	1,6	80	20	0,183
OU860650000000	65*	0,5	3,9	560	1,6	90	20	0,186
OU860700000000	70/2.3/4"	0,6	4,2	600	1,6	95	30	0,339
OU860760000000	76,2/3"	0,6	4,2	650	1,6	100	30	0,365
OU860800000000	80	0,6	4,5	690	1,6	110	30	0,384
OU860900000000	90	0,6	4,6	800	1,4	125	30	0,429
OU861000000000	100	0,6	4,8	870	1,3	140	30	0,473
OU861020000000	102/4"	0,6	4,8	880	1,3	140	30	0,482
OU861100000000	110	0,6	5,1	1010	1,2	150	30	0,692
OU861200000000	120	0,6	5,4	1210	1	160	30	0,753
OU861270000000	127/5"	0,6	5,4	1270	1	170	30	0,794
OU861300000000	130	0,7	5,7	1460	0,9	170	20	0,611
OU861400000000	140	0,7	5,7	1560	0,9	180	20	0,654
OU861500000000	151,5	0,7	5,8	1620	0,8	200	20	0,939
OU861520000000	152,4/6"	0,7	5,8	1630	0,8	200	20	0,840
OU861600000000	160	0,7	7,2	2080	0,7	220	20	0,893
OU861800000000	180	0,7	7,2	2330	0,4	250	20	1,493
OU862000000000	200	0,7	7,2	2400	0,4	260	20	1,647
OU862030000000	203,2/8"	0,7	7,2	2440	0,4	260	20	1,671
OU862500000000	250	0,8	8,0	3620	0,4	300	10	1,362
OU863000000000	300	0,8	8,2	4500	0,3	350	10	1,620

*Disponible bajo demanda. Consulte con ventas para más información y cantidades / *Available on request, contact our sales office for more info and quantities

Los datos técnicos aquí reportados fueron medidos a 23°C con 50% de humedad / The technical data here reported were measured at 23°C with 50% humidity