


EOLO PVC AF (Cod. EF 75)



Tubo en PVC plastificado en color verde, con adición de aditivos auto-extinguible y espiral de refuerzo en PVC rígido antichoque. El material especial es auto-extinguible según la UL 94-V0. Superficie interna perfectamente lisa, externa corrugada. Muy ligero y flexible. Versión antiestática (con hilo de cobre) según pedido.


- Ventilación y acondicionamiento industrial: aspiración de aire, humos y gases; industria naval.

Green flame retardant plasticized PVC hose reinforced by an anti-shock rigid PVC spiral. Inside perfectly smooth, outside corrugated. Very light and flexible. The material is flame retardant according to UL 94 V0. Antistatic version with copper wire available on request.

- Suction of air, fumes and gas; industrial ventilation systems and air conditioning plants; shipbuilding.

Espiral de PVC rígido antichoque / Anti-shock rigid PVC spiral

Tubo de PVC-P autoextinguible
Flame retardant plasticized PVC hose



Ficha técnica / Technical data

Código Code	Ø Int. Ø Int. mm/inch	Min esp. Min wall th. mm	Max esp. Max wall th. mm	Peso Weight g/m	Vacio Vac. m H ₂ O	R. de curvatura Bending mm	Lg. Rollo Coil lgth. m	Vol. Vol. m ³
EF75020000000	20*	0,8	2,7	140	2	32	50	0,054
EF75025000000	25*	0,8	2,7	170	2	32	50	0,073
EF75032000000	31,8*/1.1/4"	0,8	2,7	220	2	35	50	0,121
EF75038000000	38,1*/1.1/2"	0,8	3,0	270	2	45	50	0,141
EF75040000000	40*	0,8	3,1	300	2	50	50	0,177
EF75045000000	45*	0,8	3,4	380	2	55	50	0,199
EF75050000000	50*	0,9	3,7	460	2	60	50	0,248
EF75052000000	50,8*/2"	0,9	3,7	470	2	60	50	0,251
EF75055000000	55*	0,9	3,7	500	2	65	50	0,270
EF75060000000	60*	0,9	3,7	550	1,6	70	50	0,388
EF75063000000	63,5*/2.1/2"	0,9	3,7	580	1,6	70	50	0,408
EF75070000000	70*/2.3/4"	1,0	3,9	630	1,5	90	50	0,448
EF75076000000	76,2*/3"	1,0	3,9	690	1,5	100	50	0,605
EF75080000000	80*	1,0	4,5	820	1,5	110	50	0,641
EF75090000000	90*	1,0	4,5	920	1,5	130	30	0,428
EF75100000000	100*	1,0	4,9	1060	1,3	140	30	0,632
EF75102000000	102*/4"	1,0	4,9	1080	1,3	145	30	0,644
EF75110000000	110*	1,0	5,1	1200	1,2	150	30	0,692
EF75120000000	120*	1,0	5,1	1300	1	160	30	0,750
EF75127000000	127*/5"	1,0	5,1	1380	0,9	170	30	0,790
EF75130000000	130*	1,0	5,1	1410	0,9	170	30	1,077
EF75140000000	140*	1,0	5,3	1590	0,9	175	30	1,157
EF75150000000	151,5*	1,1	5,5	1760	0,9	180	20	0,832
EF75152000000	152,4*/6"	1,1	5,5	1770	0,9	180	20	0,837
EF75160000000	160*	1,5	6,8	2380	0,9	200	20	0,889
EF75180000000	180*	1,5	6,9	2720	0,9	220	20	1,550
EF75200000000	200*	1,6	7,4	3120	0,9	240	20	1,718
EF75203000000	203,2*/8"	1,6	7,4	3170	0,9	250	20	1,744
EF75250000000	250*	1,5	7,4	3880	0,9	280	10	1,356
EF75254000000	254*/10"	1,5	7,4	3950	0,9	290	10	1,376
EF75300000000	300*	1,5	7,6	4800	0,9	330	10	1,614

*Disponible bajo demanda. Consulte con ventas para más información y cantidades / *Available on request, contact our sales office for more info and quantities

Los datos técnicos aquí reportados fueron medidos a 23°C con 50% de humedad / The technical data here reported were measured at 23°C with 50% humidity