


NETTUNO PU

(Cod. NR)



Tubo transparente de PVC, extracto interior en TPU a base de éter y espiral de refuerzo de PVC rígido antichoque color marfil; completamente liso internamente, ligero y muy flexible. Resistente al agentes atmosféricos y la hidrólisis. Pared y sustrato de grado alimenticio, así como la espiral. Versión antiestática (con hilo de cobre) según pedido. Idóneo para el transporte de alimentos según la Regulación Europea UE 10/2011 (clase A,B,C,D2).

• Industria alimentaria: aspiración e impulsión de polvos alimentarios como harina, alimentos liofilizados, granos, especias, azúcar y piensos. Industria de bebidas: paso de bebidas con concentraciones alcohólicas de hasta el 20%.

Transparent hose made with PVC-P and ether based TPU liner, reinforced with an ivory anti-shock rigid PVC spiral. Completely smooth inside, light and very flexible. Resistant to loads, atmospherical agents and to a wide range of chemicals, as well as to Hydrolysis. Food grade hose liner, cover and rigid PVC spiral, making Nettuno PU a total food hose. The antistatic version with copper wire is available upon request. Food grade according to EU Regulation 10/2011 (classes A, B, C, D2).


• Ideal solution for suction and delivery of food powders like flours, light grains, freeze dried foodstuffs. For beverages with alcohol concentration up to 20%.



Tubo de TPU / TPU inner layer

Espiral de PVC rígido anti choque
Anti-shock rigid PVC spiral

Tubo de PVC-P / PVC hose



Ficha técnica / Technical data

Código	Ø int.	Min esp.	Max esp.	Peso	P.T.	P.R.	Vacio	R. de curvatura	Lg. Rollo	Vol.	JP
Code	Ø Int.	Min wall th.	Max wall th.	Weight	W.P.	B.P.	Vac.	Bending	Coil lgth.	Vol.	
	mm/inch	mm	mm	g/m	[bar]	[bar]	m H ₂ O	mm	m	m ³	
NR010250000000	25*	2,7	3,4	310	5,0	15	7	125	30	0,061	
NR010300000000	30*	2,8	3,5	380	5,0	15	7	150	30	0,071	
NR010320000000	31,8/1.1/4"	2,9	3,6	420	5,0	15	7	155	30	0,100	
NR010350000000	35*	3,0	3,7	470	5,0	15	7	170	30	0,109	
NR010380000000	38,1/1.1/2"	3,1	3,9	530	5,0	15	7	185	30	0,118	
NR010400000000	40	3,1	4,0	560	5,0	15	7	195	30	0,123	
NR010450000000	45*	3,1	4,3	660	5,0	15	7	215	30	0,172	
NR010500000000	50	3,3	4,7	790	5,0	15	7	235	30	0,171	NR02
NR010520000000	50,8/2"	3,3	4,7	800	5,0	15	7	235	30	0,173	
NR010550000000	55*	3,4	4,8	890	5,0	15	7	255	30	0,279	
NR010570000000	57*	3,4	4,8	930	5,0	15	7	265	30	0,288	
NR010600000000	60	3,4	4,8	970	5,0	15	7	275	30	0,301	
NR010630000000	63,5/2.1/2"	3,5	4,8	1040	5,0	15	7	290	30	0,316	
NR010650000000	65*	3,5	4,8	1060	5,0	15	7	290	30	0,322	
NR010700000000	70/2.3*/4"	3,7	5,1	1180	5,0	15	7	320	30	0,346	
NR010760000000	76,2/3"	3,9	5,4	1380	5,0	15	7	340	30	0,626	
NR010800000000	80*	4,1	5,7	1510	4,0	12	7	365	30	0,658	
NR010900000000	90*	4,4	6,0	1830	4,0	12	7	420	30	0,783	
NR011000000000	100*	4,7	6,5	2170	4,0	12	7	470	30	0,868	
NR011020000000	102/4"	4,7	6,5	2210	4,0	12	7	470	30	0,883	
NR011100000000	110*	5,1	7,0	2590	4,0	12	6	520	30	1,270	

*Disponible bajo demanda. Consulte con ventas para más información y cantidades / *Available on request, contact our sales office for more info and quantities

Los datos técnicos aquí reportados fueron medidos a 23°C con 50% de humedad / The technical data here reported were measured at 23°C with 50% humidity

JP disponible en stock / available on stock