


ZEUS PU FOOD (Cod. ZE)



Tubo transparente de TPU de base éter con espiral de refuerzo de PVC rígido anti choque de color marfil. Completamente liso internamente y externo corrugado, presenta una elevada resistencia a la abrasión, a la flexión, a los ataques de microbios, y a la hidrólisis. Espesor de pared de 1,2 mm a 2,0 mm. Alimentario según la FDA Reg. Cfr 21-Item 17.2600 (alimentos aguosos y grasos) y Reg. UE 10/2011 (clases A, B, C, D2). Espiral de calidad alimentaria. Versión antiestática (con cordón de cobre) bajo pedido.


- Industria alimentaria: aspiración y transporte de substancias alimentarias, polvos y frutos secos, gránulos y granos de diverso poder abrasivo(húmedas, secas y grasas).

***Ether based food grade TPU wall, with anti-shock rigid PVC spiral.** Smooth inside, corrugated outside. Light and flexible. Wall thickness from 1,2 mm to 2,0 mm. Resistant to Hydrolysis, microbes attacks, abrasion and flexion, this hose features high mechanical properties. Food grade according to FDA REG. Cfr 21-Item 17.2600 (acqueous and fatty food) and to EU Reg. 10/2011 (classes A, B, C, D2 and E). Food grade spiral. The antistatic version with copper wire is available on request.*

- Heavy suction and delivery of food grade powders, animal feed, granules and grains different size and abrasion power, such as sugar, salt and dry fruit. Suitable for fatty food.

Espiral de PVC rígido anti choque
Anti-shock rigid PVC spiral

TPU a base de éter
Ether based TPU



Ficha técnica / Technical data

Código	Ø int.	Min esp.	Max esp.	Peso	Vacio	R. de curvatura	Lg. Rollo	Vol.
Code	Ø Int.	Min wall th.	Max wall th.	Weight	Vac.	Bending	Coil lgth.	Vol.
	mm/inch	mm	mm	g/m	m H ₂ O	mm	m	m ³
ZE010300000000	30*	1,2	3,7	320	9	130	30	0,072
ZE010320000000	31,8/1.1/4"	1,2	3,8	350	9	140	30	0,076
ZE010350000000	35*	1,3	4,0	380	9	160	30	0,083
ZE010380000000	38,1/1.1/2"	1,3	4,0	420	9	180	30	0,118
ZE010400000000	40	1,5	4,3	500	9	190	30	0,124
ZE010450000000	45*	1,5	4,4	570	8	200	30	0,172
ZE010500000000	50*	1,5	4,8	690	8	215	30	0,172
ZE010520000000	50,8/2"	1,5	4,8	700	8	215	30	0,174
ZE010550000000	55*	1,5	4,9	780	8	225	30	0,187
ZE010570000000	57*	1,5	4,9	800	8	225	30	0,192
ZE010600000000	60	1,5	5,0	870	8	230	30	0,302
ZE010630000000	63,5/2.1/2"	1,5	5,0	920	8	240	30	0,318
ZE010650000000	65*	1,5	5,0	940	8	240	30	0,324
ZE010700000000	70/2.3/4"	1,5	5,3	950	8	250	30	0,348
ZE010760000000	76,2/3"	1,7	5,5	1120	8	270	30	0,377
ZE010800000000	80	2,0	5,9	1260	7	290	30	0,397
ZE010900000000	90	2,0	5,9	1410	7	380	30	0,586
ZE011000000000	100	2,0	6,3	1600	7	420	30	0,649
ZE011020000000	102/4"	2,0	6,3	1630	7	420	30	0,660
ZE011100000000	110*	2,0	7,6	2220	6,5	450	30	0,901
ZE011200000000	120	2,0	7,6	2410	6,5	480	30	0,973
ZE011270000000	127/5"	2,0	7,6	2540	6,5	530	30	1,092
ZE011500000000	151,2	2,0	8,1	3110	6	800	20	1,286

*Disponible bajo demanda. Consulte con ventas para más información y cantidades / *Available on request, contact our sales office for more info and quantities

Los datos técnicos aquí reportados fueron medidos a 23°C con 50% de humedad / The technical data here reported were measured at 23°C with 50% humidity