


SATURNO YELLOW (Cod. SY)



Tubo de PVC-P de color amarillo transparente con espiral de refuerzo de PVC rígido a prueba de choques de color marfil. Superficie interna completamente lisa y superficie externa semilisa. Ligero y maneable. Muy resistente al aplastamiento, a los agentes atmosféricos y a numerosas substancias químicas. Alimentaria según la Regulación Europea Reg. UE 10/2011 (clase A, B, C).


• Riegos agrícolas, aspiración e impulsión de agua y líquidos industriales, líquidos alimentarios, fertilizantes y soluciones usadas en el sector agrícola. Para camiones cisterna y maquinaria agrícola.

Transparent yellow PVC-P hose reinforced with an ivory anti-shock rigid PVC spiral. Inside surface smooth, light corrugation outside. Strong and flexible, resistant to crushing, atmospheric agents and most chemicals. Suitable for suction and delivery of food liquids, according to EU 10/2011 (classes A, B, C).

• Excellent in agriculture, for irrigation and suction of liquids, fertilizers and solutions used in agriculture. Used on tank trucks

Espiral de PVC rígido anti choque
Anti-shock rigid PVC spiral

Tubo de PVC-P / PVC hose



Ficha técnica / Technical data

Código Code	Ø int. Ø Int.	Min esp. Min wall th.	Max esp. Max wall th.	Peso Weight	P.T. W.P.	P.R. B.P.	Vacio Vac.	R. de curvatura Bending	Lg. Rollo Coil lgth.	Vol. Vol.
	mm/inch	mm	mm	g/m	[bar]	[bar]	m H ₂ O	mm	m	m ³
SY010190000000	19,1/3/4"	2,2	2,9	200	5,0	15	6	110	50	0,046
SY010200000000	20	2,2	2,9	210	5,0	15	6	110	50	0,048
SY010220000000	22	2,3	3,0	240	5,0	15	6	130	50	0,061
SY010250000000	25	2,3	3,0	270	5,0	15	6	140	50	0,078
SY010255000000	25,5	2,3	3,0	280	5,0	15	6	140	50	0,079
SY010300000000	30	2,3	3,1	330	5,0	15	6	170	50	0,116
SY010320000000	31,8/1.1/4"	2,4	3,2	360	5,0	15	6	180	50	0,122
SY010325000000	32,5	2,4	3,2	370	5,0	15	6	180	50	0,124
SY010350000000	35	2,5	3,3	410	5,0	15	6	195	50	0,133
SY010380000000	38,1/1.1/2"	2,6	3,4	460	5,0	15	6	210	50	0,172
SY010390000000	39	2,6	3,4	470	5,0	15	6	215	50	0,176
SY010400000000	40	2,6	3,5	490	5,0	15	6	220	50	0,180
SY010450000000	45	2,7	3,6	570	5,0	15	6	250	50	0,234
SY010500000000	50	3,0	4,0	710	5,0	15	6	270	50	0,251
SY010520000000	50,8/2"	3,0	4,0	720	5,0	15	6	270	50	0,254
SY010550000000	55	3,0	4,0	780	5,0	15	6	310	50	0,363
SY010570000000	57	3,0	4,0	800	5,0	15	6	310	50	0,374
SY010600000000	60	3,0	4,2	870	5,0	15	6	330	50	0,394
SY010630000000	63,5/2.1/2"	3,0	4,2	920	5,0	15	6	350	50	0,414
SY010650000000	65	3,1	4,3	970	5,0	15	6	360	50	0,636
SY010700000000	70/2.3/4"	3,2	4,5	1050	4,0	12	6	450	50	0,683
SY010750000000	75	3,3	4,6	1160	4,0	12	6	500	50	0,727
SY010760000000	76,2/3"	3,3	4,6	1180	4,0	12	6	500	50	0,738
SY010800000000	80	3,6	5,0	1350	4,0	12	6	550	50	0,778
SY010900000000	90	4,2	6,0	1870	3,0	9	6	630	30	0,588
SY011000000000	100	4,6	6,4	2210	3,0	9	6	710	30	0,866
SY011020000000	102/4"	4,6	6,4	2250	3,0	9	6	710	30	0,882
SY011100000000	110	5,0	6,7	2560	3,0	9	6	720	30	1,264
SY011200000000	120	5,0	6,8	2810	3,0	9	6	730	30	1,368
SY011270000000	127/5"	5,1	6,9	3030	3,0	9	6	740	30	1,442
SY011500000000	151,5	5,9	7,8	4160	3,0	9	6	800	20	1,337
SY011520000000	152,4/6"	5,9	7,8	4180	3,0	9	6	800	20	1,344
SY012000000000	200	6,5	10,0	6510	2,0	6	4,5	1000	10	1,760

*Disponibile bajo demanda. Consulte con ventas para más información y cantidades / *Available on request, contact our sales office for more info and quantities

Los datos técnicos aquí reportados fueron medidos a 23°C con 50% de humedad / The technical data here reported were measured at 23°C with 50% humidity