


APOLLO OIL (Cod. Ol 01)



Tubo de PVC/NBR de color azul, reforzado con espiral de PVC rígido antichoque. Interno liso y externo ligeramente corrugado. Muy resistente al aplastamiento, a la abrasión, a los agentes atmosféricos y a numerosas sustancias químicas. Versión antiestática (con hilo de cobre) según pedido. Para derivados petrolíferos (no sólo petróleo).

- Aspiración y impulsión de hidrocarburos: aceites minerales, lubricantes, carburantes crudos (nafta, gasolio) y como línea de retorno de circuitos hidráulicos.


Blue PVC-NBR hose manufactured incorporating a spiral reinforcement of anti-shock rigid PVC. Inside surface smooth, light corrugated outside. Very strong and resistant to crushing, abrasion, atmospheric agents and most chemicals. Petrol base products (not solely petrol). On request, It can be manufactured in the antistatic version with copper wire.

- Suction and delivery of mineral oils, lubricants, crude fuel (naphta, diesel oil) and as a return line in hydraulic systems



Espiral de PVC rígido antichoque / Anti-shock rigid PVC spiral

Tubo de PVC/NBR / PVC/NBR hose



Ficha técnica / Technical data

Código	Ø int.	Min esp.	Max esp.	Peso	P.T.	P.R.	Vacio	R. de curvatura	Lg. Rollo	Vol.
Code	Ø Int.	Min wall th.	Max wall th.	Weight	W.P.	B.P.	Vac.	Bending	Coil lgth.	Vol.
	mm/inch	mm	mm	g/m	[bar]	[bar]	m H ₂ O	mm	m	m ³
01010200000000	20*	3,2	3,5	290	7,0	21	10	80	50	0,069
01010250000000	25*	3,4	3,8	390	6,0	18	10	100	50	0,083
01010254000000	25,4*/1"	3,4	3,8	400	6,0	18	10	100	50	0,084
01010320000000	31,8*/1.1/4"	4,0	4,4	590	6,0	18	10	130	50	0,130
01010380000000	38,1*/1.1/2"	3,9	4,5	670	5,0	15	10	155	50	0,203
01010400000000	40*	3,9	4,5	700	5,0	15	10	160	50	0,212
01010520000000	50,8*/2"	4,3	4,9	970	4,0	12	10	200	50	0,262
01010550000000	55*	4,5	5,1	1100	4,0	12	9	220	50	0,376
01010600000000	60*	4,7	5,4	1270	4,0	12	9	260	50	0,408
01010630000000	63,5*/2.1/2"	4,8	5,5	1370	4,0	12	9	260	50	0,429
01010700000000	70*/2.3/4"	4,9	5,6	1490	3,0	9	9	350	50	0,585
01010760000000	76,2*/3"	5,0	5,7	1660	3,0	9	9	310	50	0,631
01010800000000	80*	5,2	6,0	1810	3,0	9	9	400	50	0,795
01010900000000	90*	5,4	6,3	2110	3,0	9	9	360	30	0,591
01011020000000	102*/4"	6,0	7,1	2680	3,0	9	8,5	410	30	0,837
01011270000000	127*/5"	6,4	7,5	3510	2,5	7,5	8	510	30	1,091
01011520000000	152,4*/6"	7,4	8,7	4930	2,0	6	8	610	20	1,358
01012030000000	203,2*/8"	10,9	12,9	10010	1,5	4,5	7	850	10	1,832

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite / *Available on request, contact our sales office for more info and quantities

I dati tecnici qui riportati sono stati misurati a 23°C e al 50% di umidità / The technical data here reported were measured at 23°C with 50% humidity