

Codice	Ø Int.	Spess. Min.	Spess. Max	Peso	P.E.	P.S.	Depr.	R. Curvatura	Lg. Rotolo	Vol.
Code	Ø Int.	Min wall th.	Max wall th.	Weight	W.P.	B.P.	Vac.	Bending	Coil lgth.	Vol.
	mm/inch	mm	mm	g/m	[bar]	[bar]	m H ₂ O	mm	m	m ³
01010200000000	20*	3,2	3,5	290	7,0	21	10	80	50	0,069
01010250000000	25*	3,4	3,8	390	6,0	18	10	100	50	0,083
01010254000000	25,4*/1"	3,4	3,8	400	6,0	18	10	100	50	0,084
01010320000000	31,8*/1.1/4"	4,0	4,4	590	6,0	18	10	130	50	0,130
01010380000000	38,1*/1.1/2"	3,9	4,5	670	5,0	15	10	155	50	0,203
01010400000000	40*	3,9	4,5	700	5,0	15	10	160	50	0,212
01010520000000	50,8*/2"	4,3	4,9	970	4,0	12	10	200	50	0,262
01010550000000	55*	4,5	5,1	1100	4,0	12	9	220	50	0,376
01010600000000	60*	4,7	5,4	1270	4,0	12	9	260	50	0,408
01010630000000	63,5*/2.1/2"	4,8	5,5	1370	4,0	12	9	260	50	0,429
01010700000000	70*/2.3/4"	4,9	5,6	1490	3,0	9	9	350	50	0,585
01010760000000	76,2*/3"	5,0	5,7	1660	3,0	9	9	310	50	0,631
01010800000000	80*	5,2	6,0	1810	3,0	9	9	400	50	0,795
01010900000000	90*	5,4	6,3	2110	3,0	9	9	360	30	0,591
01011020000000	102*/4"	6,0	7,1	2680	3,0	9	8,5	410	30	0,837
01011270000000	127*/5"	6,4	7,5	3510	2,5	7,5	8	510	30	1,091
01011520000000	152,4*/6"	7,4	8,7	4930	2,0	6	8	610	20	1,358
01012030000000	203,2*/8"	10,9	12,9	10010	1,5	4,5	7	850	10	1,832

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite / *Available on request,contact our sales office for more info and quantities

I dati tecnici qui riportati sono stati misurati a 23°C e al 50% di umidità / The technical data here reported were measured at 23°c with 50% humidity