



SATURNO L SE

(Cod. XL 06)



3 variantes de color
3 colour versions



Tubo de PVC-P verde transparente con espiral de refuerzo de PVC rígido a prueba de choques de color marfil. Superficie interna lisa y superficie externa semilisa. Mantiene una buena flexibilidad incluso a bajas temperaturas. Ligero y maneable. Muy resistente al aplastamiento, a la abrasión, a los agentes atmosféricos y a numerosas sustancias químicas.


• Para riego, aspiración y transporte de líquidos en general y soluciones usadas en el sector agrícola.

Transparent green PVC-P hose reinforced with a green anti-shock rigid PVC spiral. Inside surface smooth, light corrugation outside. Very flexible even at low temperatures. Strong, resistant to crushing, atmospheric agents and most chemicals.

• Excellent in agriculture, for irrigation and suction of liquids; suitable to be used on slurry machines. Different colour versions available on request.

Espiral de PVC rígido antichoque
Anti-shock rigid PVC spiral

Tubo de PVC-P / PVC hose



Ficha técnica / Technical data

Código	Ø int.	Min esp.	Max esp.	Peso	P.T.	P.R.	Vacio	R. de curvatura	Lg. Rollo	Vol.
Code	Ø Int.	Min wall th.	Max wall th.	Weight	W.P.	B.P.	Vac.	Bending	Coil lgth.	Vol.
	mm/inch	mm	mm	g/m	[bar]	[bar]	m H ₂ O	mm	m	m ³
XL060190000000	19,1*/3/4"	2,2	2,9	200	5,0	15	6	110	50	0,046
XL060200000000	20	2,2	2,9	210	5,0	15	6	110	50	0,048
XL060220000000	22*	2,3	3,0	240	5,0	15	6	130	50	0,061
XL060250000000	25	2,3	3,0	270	5,0	15	6	140	50	0,078
XL060255000000	25,5*	2,3	3,0	270	5,0	15	6	140	50	0,079
XL060300000000	30	2,3	3,1	320	5,0	15	6	170	50	0,116
XL060320000000	31,8/1.1/4"	2,4	3,2	360	5,0	15	6	180	50	0,122
XL060325000000	32,5*	2,4	3,2	370	5,0	15	6	180	50	0,124
XL060350000000	35*	2,5	3,3	400	5,0	15	6	195	50	0,133
XL060380000000	38,1/1.1/2"	2,6	3,4	450	5,0	15	6	210	50	0,172
XL060390000000	39*	2,6	3,4	460	5,0	15	6	215	50	0,176
XL060400000000	40	2,6	3,5	480	5,0	15	6	220	50	0,180
XL060450000000	45*	2,7	3,6	560	5,0	15	6	250	50	0,226
XL060500000000	50	3,0	4,0	700	5,0	15	6	270	50	0,251
XL060520000000	50,8/2"	3,0	4,0	710	5,0	15	6	270	50	0,254
XL060550000000	55*	3,0	4,0	760	5,0	15	6	310	50	0,454
XL060570000000	57*	3,0	4,0	790	5,0	15	6	310	50	0,374
XL060600000000	60	3,0	4,2	860	5,0	15	6	330	50	0,394
XL060630000000	63,5/2.1/2"	3,0	4,2	910	5,0	15	6	350	50	0,414
XL060650000000	65*	3,1	4,3	960	5,0	15	6	360	50	0,636
XL060700000000	70*/2.3/4"	3,2	4,5	1040	4,0	12	6	450	50	0,683
XL060750000000	75*	3,3	4,6	1140	4,0	12	6	500	50	0,727
XL060760000000	76,2/3"	3,3	4,6	1160	4,0	12	6	500	50	0,738
XL060800000000	80	3,6	5,0	1330	4,0	12	6	550	50	0,922
XL060900000000	90*	4,2	6,0	1840	3,0	9	6	630	30	0,588
XL061000000000	100	4,6	6,4	2180	3,0	9	6	710	30	0,866
XL061020000000	102/4"	4,6	6,4	2220	3,0	9	6	710	30	0,882
XL061100000000	110*	5,0	6,7	2530	3,0	9	6	720	30	1,264
XL061200000000	120*	5,0	6,8	2770	3,0	9	6	730	30	1,368
XL061250000000	125*	5,1	6,9	2950	3,0	9	6	740	30	1,421
XL061270000000	127*/5"	5,1	6,9	2990	3,0	9	6	740	30	1,442
XL061500000000	151,5*	5,9	7,8	4100	3,0	9	6	800	20	1,337
XL061520000000	152,4*/6"	5,9	7,8	4120	3,0	9	6	800	20	1,344
XL062000000000	200*	6,5	10,0	6420	2,0	6	4,5	1000	10	1,760
XL062030000000	203,2*/8"	6,5	10,0	6520	2,0	6	4,5	1000	10	1,786

*Disponible bajo demanda. Consulte con ventas para más información y cantidades / *Available on request, contact our sales office for more info and quantities

Los datos técnicos aquí reportados fueron medidos a 23°C con 50% de humedad / The technical data here reported were measured at 23°C with 50% humidity