

Codice	Ø Int.	Spess. Min.	Spess. Max	Peso	P.E.	P.S.	Depr.	R. Curvatura	Lg. Rotolo	Vol.
Code	Ø Int.	Min wall th.	Max wall th.	Weight	W.P.	B.P.	Vac.	Bending	Coil lgth.	Vol.
	mm/inch	mm	mm	g/m	[bar]	[bar]	m H ₂ O	mm	m	m ³
SI060160000000	16*	3,3	3,4	250	6,0	18	10	40	30	0,030
SI060200000000	20*	3,3	3,4	300	6,0	18	10	50	30	0,037
SI060250000000	25*	3,4	3,5	370	6,0	18	10	60	30	0,049
SI060300000000	30*	3,4	3,5	430	5,0	15	10	80	30	0,080
SI060320000000	31,8*/1.1/4"	3,4	3,5	460	5,0	15	10	80	30	0,084
SI060380000000	38,1*/1.1/2"	3,4	3,5	540	5,0	15	10	100	30	0,097
SI060400000000	40*	3,4	3,5	560	5,0	15	10	100	30	0,102
SI060450000000	45*	3,9	4,0	730	5,0	15	10	110	30	0,136
SI060500000000	50*	3,9	4,0	810	5,0	15	10	130	30	0,148
SI060515000000	51,5*	3,9	4,0	830	5,0	15	10	130	30	0,152
SI060650000000	65*	3,9	4,1	1040	4,0	12	10	160	30	0,234

***Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite / *Available on request,contact our sales office for more info and quantities**

I dati tecnici qui riportati sono stati misurati a 23°C e al 50% di umidità / The technical data here reported were measured at 23°C with 50% humidity