

# FICHA TÉCNICA · TECHNICAL DATA



en stock  
available on stock




+60°C


-10°C

3,2-11,2

## ARTÍCULOS DE LA MISMA SERIE ITEMS IN THE SAME SERIES



NETTUNO ENO (cód. NQ EN) p.109



SPIRALPRESS ENO (cód. BS EN) p.111

CÓDIGO CODE	Ø INT. Ø INT.	MIN ESP. MIN WALL TH.	MAX ESP. MAX WALL TH.	PESO WEIGHT	P.T. W.P.	P.R. B.P.	VACIO VACUUM	R. CURVATURA BENDING	LG. ROLLO COIL LGTH.	VOLUMEN VOLUME
	mm	mm	mm	g/m	bar	bar	m H <sub>2</sub> O	mm	m	m <sup>3</sup>
BF010190000000*	19,1	3,2	3,5	290	9	27	10	110	50	0,084
BF010200000000	20	3,2	3,5	300	9	27	10	110	50	0,104
BF010250000000	25	3,3	3,7	390	8	24	10	170	50	0,083
BF010300000000	30	3,5	3,9	490	8	24	10	190	50	0,121
BF010320000000	31,8	3,5	3,9	510	7	21	10	230	50	0,127
BF010350000000	35	3,7	4,2	590	7	21	10	230	50	0,167
BF010380000000	38,1	4,1	4,5	710	7	21	10	260	50	0,211
BF010390000000*	39	4,1	4,6	740	7	21	10	265	50	0,216
BF010400000000	40	4,1	4,6	750	7	21	10	270	50	0,220
BF010450000000*	45	4,4	4,9	910	7	21	10	310	50	0,237
BF010500000000	50	4,7	5,3	1090	6	18	10	350	50	0,349
BF010515000000*	51,5	4,8	5,3	1130	6	18	10	360	50	0,358
BF010520000000	50,8	4,7	5,3	1100	6	18	10	350	50	0,354
BF010550000000*	55	5	5,5	1260	6	18	10	370	50	0,570
BF010600000000	60	5,2	5,8	1440	6	18	10	415	50	0,619
BF010630000000*	63,5	5,5	6,1	1620	6	18	10	440	50	0,654
BF010650000000*	65	5,5	6,1	1660	6	18	10	450	50	0,667
BF010700000000*	70	5,6	6,3	1780	5	15	10	480	50	0,714
BF010760000000	76,2	5,7	6,3	1950	5	15	10	525	50	0,767
BF010800000000	80	6,1	6,8	2180	5	15	10	555	30 (JP 30/50)	0,674
BF010900000000*	90	6,4	7,1	2570	5	15	10	630	30	0,750
BF011000000000	100	7,3	8,1	3270	5	15	9	695	30	0,892
BF011020000000	102	7,3	8,1	3330	5	15	9	695	30	0,908
BF011100000000*	110	7,4	8,2	3610	4	12	9	780	30	1,294
BF011200000000	120	7,8	8,6	4160	4	12	9	900	30	1,405
BF011270000000*	127	7,7	8,6	4350	4	12	9	1000	30	1,730
BF011500000000*	151,5	9,3	10,3	6340	4	12	8,5	1300	20	1,666
BF011520000000*	152,8	9,3	10,3	6390	4	12	8,5	1300	20	1,679
BF012000000000*	200	11,2	13,2	10350	4	12	8	2100	10	2,192
BF012030000000*	203,2	11,2	13,2	10510	4	12	8	2100	10	2,223

\*Disponible bajo pedido, para cantidades a convenir con el departamento de ventas.

\*Available on request, contact our sales office for more info and quantities.

Los datos técnicos indicados se midieron a 23°C y 50% de humedad.

The technical data here reported have been measured at 23°C with 50% umidity.