

SCHEDA TECNICA · TECHNICAL DATA



disponibile a magazzino
available on stock



+50°C

-40°C

ARTICOLI DELLA STESSA SERIE
ITEMS IN THE SAME SERIES



APOLLO SUPERFLEX (cod. AS) p.70

CODICE CODE	Ø INT. Ø INT.	SPESS. MIN. MIN WALL TH.	SPESS. MAX. MAX WALL TH.	PESO WEIGHT	P.E. W.P.	P.S. B.P.	DEPR. VACUUM	R. CURVATURA BENDING	LG. ROTOLO COIL LGTH.	VOLUME
	mm	mm	mm	g/m	bar	bar	m H ₂ O	m ²	m	m ³
SF010520000000	50,8	4,4	4,9	970	3,3	10	9	160	50	0,262
SF010550000000*	55	4,6	5,1	1100	3,3	10	9	160	50	0,282
SF010600000000*	60	4,8	5,3	1260	3	9	9	200	50	0,407
SF010630000000	63,5	4,9	5,5	1380	3	9	9	210	50	0,429
SF010650000000*	65	5	5,6	1440	3	9	9	210	50	0,439
SF010700000000*	70	5,1	5,7	1530	3	9	9	225	50	0,469
SF010760000000	76,2	5,1	5,8	1670	3	9	9	250	50	0,632
SF010800000000	80	5,1	6,8	1930	2,5	7,5	9	270	50	0,674
SF010900000000	90	5,2	7	2220	2,5	7,5	9	300	30	0,599
SF011020000000	102	5,9	7,6	2770	2,2	6,5	9	335	30	0,675
SF011050000000	105	6	7,6	2870	2,2	6,5	9	335	30	0,692
SF011100000000	110	6,1	7,6	2990	2	6	8	360	30	0,721
SF011270000000	127	6,3	7,8	3540	1,8	5,5	8	410	30	1,095
SF011520000000	152,4	7,4	9	5000	1,5	4,5	8	500	20	1,309

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite.

*Available on request, contact our sales office for more info and quantities.

I dati tecnici riportati sono stati misurati a 23°C e al 50% di umidità.

The technical data here reported have been measured at 23°C with 50% humidity.