

VULCANO® 12 ET



(ES) Tubo translucido de TPU a base de éter, reforzado con espiral de acero recubierto de TPU de color gris, para asegurar la máxima adhesión con la pared. Realizado con un TPU especial dotado de características combinadas que convierten el material de la pared en antiestático permanente ($R < 10^9 \text{ Ohm/m}$). Superficie interna lisa para optimizar el flujo, espesor de pared de 1,2 mm constante para todos los diámetros. Excelente resistencia a la hidrólisis y a los microbios, a la intemperie y a los rayos UV; sin olor, no altera las propiedades organolépticas de los productos transportados. Conductivo ($R < 10^2 \text{ Ohm/m}$) conectando la espiral a tierra. Alimentario según UE 10/2011 (clases A, B, C, D1, D2, E) y FDA CFR 21-177.2600.

• Aspiración media de sustancias abrasivas en la industria alimentaria y farmacéutica; se utiliza en aspiradoras industriales, barredoras y equipos de limpieza urbana.

(EN) Translucent ether based food grade TPU hose reinforced with a grey coloured TPU coated high adhesion steel spiral. The wall material is permanent antistatic ($R < 10^9 \text{ Ohm/m}$). Smooth inside to ensure optimization of flow properties. Constant wall thickness of 1,2 mm for the whole diameter range. Resistant to microbes and to Hydrolysis, to UV rays and weathering. Food grade, according to EU 10/2011 (classes A, B, C, D1, D2, E) and FDA CFR 21-177.2600. The hose is neutral in odor and taste and does not alter the organoleptical properties of the transferred materials. It can be made conductive ($R < 10^2 \text{ Ohm/m}$) by grounding the spiral.

• Suction of abrasive powders and substances in Food processing and pharma plants. Used on lawnmowing machines and street cleaning vehicles.

CÓD. VO
Ø mm 25-500

TPU a base de éter
Ether-based TPU

Espiral de acero recubierta de TPU de color gris
Grey colored TPU coated steel spiral



FICHA TÉCNICA · TECHNICAL DATA		CÓDIGO CODE	Ø INT. Ø INT.	MIN ESP. MIN WALL TH.	PESO WEIGHT	VACÍO VACUUM	R. CURVATURA BENDING	LG. ROLLO COIL LGTH.	VOL. VOL.	ABRAZADERAS DOBLE PUENTE W2 DOUBLE BRIDGE W2
			mm	mm	g/m	m H ₂ O	mm	m	m ³	
 F2 W2 p.122 Abrazaderas doble puente W2 / Double bridge W2		V001025000000*	25	1,2	245	6	30	20	0,046	-
		V001030000000*	30	1,2	345	6	35	20	0,054	-
		V001032000000*	32	1,2	365	6	35	20	0,057	-
		V001035000000*	35	1,2	395	6	40	20	0,062	-
		V001038000000*	38	1,2	385	6	40	20	0,066	-
		V001040000000*	40	1,2	405	6	50	20	0,086	-
		V001045000000*	45	1,2	450	6	50	20	0,095	-
		V001050000000	50	1,2	495	5	60	20	0,104	-
		V001051000000	51	1,2	505	5	60	20	0,106	-
		V001060000000*	60	1,2	640	4,5	70	20	0,131	-
ARTÍCULOS DE LA MISMA SERIE ITEMS IN THE SAME SERIES VULCANO 09 ET (cód. VK) p.87		V001063000000	63	1,2	670	4,5	70	20	0,182	-
		V001065000000*	65	1,2	690	4,5	70	20	0,187	-
		V001070000000	70	1,2	845	4,5	80	20	0,202	-
		V001075000000*	75	1,2	900	4	80	20	0,215	-
		V001076000000	76	1,2	910	4	90	20	0,217	-
		V001080000000	80	1,2	955	3,5	90	20	0,227	F2 W2 076.0 090.0
		V001090000000	90	1,2	1070	3	100	20	0,285	-
		V001100000000*	100	1,2	1185	2,5	120	15	0,313	-
		V001102000000	102	1,2	1295	2,5	120	15	0,319	-
		V001110000000	110	1,2	1410	2,5	130	15	0,343	F2 W2 100.0 127.0
 VULCANO 15 ET (cód. VI) p.89		V001120000000*	120	1,2	1545	2	140	15	0,372	-
		V001127000000	127	1,2	1630	2	150	15	0,392	-
		V001130000000*	130	1,2	1670	2	150	15	0,401	-
		V001140000000*	140	1,2	1795	1,5	160	15	0,645	-
		V001150000000*	150	1,2	1915	1,5	170	15	0,688	-
		V001152000000	152	1,2	1940	1,5	170	15	0,696	F2 W2 130.0 190.0
		V001160000000*	160	1,2	2040	1,5	180	15	0,731	-
		V001170000000*	170	1,2	1950	1	200	15	0,922	-
		V001180000000*	180	1,2	2060	1	210	15	0,973	-
		V001200000000*	200	1,2	2285	1	230	15	1,075	-
		V001203000000*	203	1,2	2315	0,5	230	15	1,091	-
		V001205000000*	205	1,2	2340	0,5	230	15	1,101	F2 W2 200.0 230.0
		V001220000000*	220	1,2	2505	0,5	260	10	1,178	-
		V001228000000*	228	1,2	2595	0,5	260	10	1,219	-
		V001250000000*	250	1,2	2840	0,5	290	10	1,331	-
		V001254000000*	254	1,2	2885	0,5	290	10	1,352	-
		V001265000000*	265	1,2	3380	0,5	300	10	1,409	-
		V001279000000*	279	1,2	3555	0,5	320	10	1,481	F2 W2 250.0 330.0
		V001305000000*	305	1,2	3880	0,5	350	10	1,614	-
		V001355000000*	355	1,2	4505	0,5	410	tramo 10 m/ straight	1,334	-
		V001406000000*	406	1,2	6250	0,4	500	tramo 10 m/ straight	1,732	-
		V001500000000*	500	1,2	7690	0,3	600	tramo 6 m/ straight	1,568	-

*Disponible bajo pedido, para cantidades a convenir con el departamento de ventas.

*Available on request, contact our sales office for more info and quantities.

Los datos técnicos indicados se midieron a 23°C y 50% de humedad.

The technical data here reported have been measured at 23°C with 50% humidity.