

APOLLO TOTAL

PVC / NBR

La solución más ligera y flexible de toda la gama Apollo

ES

Tubo de PVC/NBR de color negro, reforzado con espiral de PVC rígido antichoque verde. Formulación específica para climas muy rígidos que lo convierten en un tubo mejor que otros análogos en PVC usados comunmente. Estructura con espiral a vista que garantiza un deslizamiento fácil sobre el terreno. Versión antiestática con hilo de cobre (cód. TL 02) disponible bajo pedido.

- Óptimo para aspiración e impulsión de líquidos en general y especialmente para la aspiración y descarga de aguas residuales, incluso a temperaturas muy bajas.

EN

PVC/NBR hose reinforced with a green anti-shock rigid PVC spiral. Its particular mixed rubber nitrilic formulation gives it the highest flexibility at extreme low temperatures. Its profile with a slightly protruding spiral guarantees an easy dragging on the ground and an easy and safe connection. AS version with copper wire on request (Cod. TL 02).

- Suction and delivery of liquids and waste water in general; ideal to be used on tank trucks, even at extremely low temperatures.



CÓD. TL 01

Ø mm 40-152

Espiral de PVC rígido antichoque ligeramente a vista
Slightly exposed anti-shock rigid PVC spiral



Tubo en PVC-NBR
PVC-NBR hose

FICHA TÉCNICA · TECHNICAL DATA	CÓDIGO	Ø INT.	MIN ESP.	MAX ESP.	PESO	P.T.	P.R.	VACIO	R. CURVATURA	LG. ROLLO	VOLUME
	CODE	Ø INT.	MIN WALL TH.	MAX WALL TH.	WEIGHT	W.P.	B.P.	VACUUM	BENDING	COIL LGTH.	VOLUME
		mm	mm	mm	g/m	bar	bar	m H ₂ O	m ²	m	m ³
 <p>en stock available on stock</p>   <p>ARTÍCULOS DE LA MISMA SERIE ITEMS IN THE SAME SERIES</p>  <p>APOLLO SUPERFLEX 2 (cód. AS) p.71</p>	TL01040000000*	40	3,5	4,1	620	3,3	10	9	120	50	0,208
	TL01045000000*	45	3,6	4,4	730	3,3	10	9	130	50	0,232
	TL01052000000*	50,8	3,8	4,7	880	3,3	10	9	145	50	0,260
	TL01063000000*	63,5	3,9	5,4	1220	3,0	9	9	200	50	0,535
	TL01076000000*	76,2	4,0	6,0	1530	2,5	7,5	9	225	50	0,635
	TL01800000000*	80	4,0	6,9	1840	2,5	7,5	9	225	50	0,675
	TL01090000000*	90	4,2	7,2	2150	2,2	6,5	9	270	50	0,752
	TL01102000000*	102	4,8	7,7	2650	2,2	6,5	9	300	30	0,676
	TL01127000000*	127	5,1	7,8	3290	2,0	6	9	400	30	0,821
	TL01152000000*	152,4	6,0	9,0	4690	2,0	6	9	460	30	0,982

*Disponible bajo pedido, para cantidades a convenir con el departamento de ventas.

*Available on request, contact our sales office for more info and quantities.

Los datos técnicos indicados se midieron a 23°C y 50% de humedad.

The technical data here reported have been measured at 23°C with 50% humidity.