


SCHEDA TECNICA · TECHNICAL DATA

3-3,5

+80°C

-10°C




SC WT p.125


Spiralina rossa/ Red banding coil

ARTICOLI DELLA STESSA SERIE

ITEMS IN THE SAME SERIES



SPIRALPRESS WT (cod. WT) p.72



SPIRALPRESS ENO (cod. BS EN) p.111

CODICE	Ø INT.	SPESS. MIN.	SPESS. MAX.	PESO	P.E.	DEPR.	R. CURVATURA	LG. ROTOLO	VOLUME	LG. SPIRALINA
CODE	Ø INT.	MIN WALL TH.	MAX WALL TH.	WEIGHT	W.P.	VACUUM	BENDING	COIL LGTH.	VOLUME	BANDING COIL LGTH.
	mm	mm	mm	g/m	bar 23°c/ 80°c	m H ₂ O	mm	m	m³	mm
SK010380000000*	38,1/ 1 1/2"	3	7,1	820	8/2,5	9,5	90	30	0,134	153
SK010400000000*	40	3	7,1	840	8/2,5	9,5	100	30	0,139	152
SK010500000000*	50	3	7,7	1125	7/2,5	9,5	160	30	0,251	180
SK010508000000*	50,8/ 2"	3	7,7	1140	7/2,5	9,5	160	30	0,254	180
SK010600000000*	60	3	8,4	1280	7/2,5	9,5	180	30	0,332	203
SK010635000000*	63,5/ 2 1/2"	3	8,4	1350	7/2,5	9,5	210	30	0,347	203
SK010760000000*	76,3/ 3"	3,5	9,8	1975	6/2	9	200	30	0,414	225
SK010800000000*	80	3,5	10,4	2255	6/2	9	210	30	0,581	225
SK011000000000*	100	3,5	10,4	2675	6/2	9	300	30	0,928	240
SK011020000000*	101,6/ 4"	3,5	10,5	2750	6/2	9	300	30	0,942	240

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite.

*Available on request,contact our sales office for more info and quantities.

I dati tecnici riportati sono stati misurati a 23°C e al 50% di umidità.

The technical data here reported have been measured at 23°C with 50% umidity.